



# OUR ELBOWS ARE EASY ON YOURS

Choose SpeedCouple pre-installed elbow coupling

*Available on  
rigid steel elbows*

*Standard &  
special radius*

*Trade sizes 2-5*

*Listed as  
concrete tight*

Installing elbows in tight spaces is easy with SpeedCouple. Just turn the coupling, not the elbow, and let the lead-in threads do most of the work. You'll finish the job faster and without fatigue.

Watch the video at [picoma.com/speedcouple](http://picoma.com/speedcouple)

AMERICAN  
METAL



**picoma**<sup>®</sup>  
A DIVISION OF ZEKELMAN INDUSTRIES



# SpeedCouple Pre-installed Coupling

- Fast, easy installation in tight spaces
- Lead-in threads for quick connecting
- Listed as concrete tight

## SPEEDCOUPLE 90° RIGID ELBOW WEIGHTS, DIMENSIONS AND PACKAGING

TRADE SIZE	MIN. RADIUS	OFFSET	STRAIGHT	WEIGHT PER ELBOW	WEIGHT PER ELBOW WITH COUPLING	STANDARD CARTON QTY.
	in.	in.	in.	lbs.	lbs.	
2	9.5	14.54	5.04	6.70	7.58	5
2½	10.5	17.00	6.50	12.00	13.76	Bulk
3	13	19.67	6.67	19.00	20.98	Bulk
3½	15	22.72	7.72	28.00	30.65	Bulk
4	16	23.94	7.94	31.00	34.09	Bulk
5	24	34.90	10.90	68.00	71.97	Bulk


*SpeedCouple elbows shall be listed to safety standards UL-6 and UL-514B. Elbows manufactured in accordance with ANSI® C80.1.*

*Standard-radius elbows: Available in 90°, 60°, 45°, 30°, 22½°, 15°, 11¼°*

*Special-radius elbows: Available in 90°, 60°, 45°, 30°, 22½°, 15°, 11¼°*

Watch the video at [picoma.com/speedcouple](http://picoma.com/speedcouple)

PIC-060520


 9208 Jeffrey Drive  
 Cambridge, OH 43725  
 P 800.PICOMA1  
 F 740.439.4160

[info@picoma.com](mailto:info@picoma.com)  
[picoma.com](http://picoma.com)

