



OUR ELBOWS ARE EASY ON YOURS

Choose SpeedCouple pre-installed elbow coupling

*Available on
rigid steel elbows*

*Standard &
special radius*

Trade sizes 2-6

*Listed as
concrete tight*

Installing elbows in tight spaces is easy with SpeedCouple. Just turn the coupling, not the elbow, and let the lead-in threads do most of the work. You'll finish the job faster and without fatigue.

Watch the video at picoma.com/speedcouple

AMERICAN
METAL



picoma[®]
A ZEKELMAN COMPANY



SpeedCouple Pre-installed Coupling

- Fast, easy installation in tight spaces
- Lead-in threads for quick connecting
- Listed as concrete tight

SPEEDCOUPLE 90° RIGID ELBOW WEIGHTS, DIMENSIONS AND PACKAGING

TRADE SIZE	MIN. RADIUS	OFFSET	STRAIGHT	WEIGHT PER ELBOW	WEIGHT PER ELBOW WITH COUPLING	STANDARD CARTON QTY.
	in.	in.	in.	lbs.	lbs.	
2	9.5	14.54	5.04	6.70	7.58	5
2½	10.5	17.00	6.50	12.00	13.76	Bulk
3	13	19.67	6.67	19.00	20.98	Bulk
3½	15	22.72	7.72	28.00	30.65	Bulk
4	16	23.94	7.94	31.00	34.09	Bulk
5	24	34.90	10.90	68.00	71.97	Bulk
6	30	45.50	15.50	114.00	119.25	Bulk


SpeedCouple elbows shall be listed to safety standards UL-6 and UL-514B. Elbows manufactured in accordance with ANSI® C80.1.

Standard-radius elbows: Available in 90°, 60°, 45°, 30°, 22½°, 15°, 11¼°

Special-radius elbows: Available in 90°, 60°, 45°, 30°, 22½°, 15°, 11¼°

Watch the video at picoma.com/speedcouple

PIC-010424

 9208 Jeffrey Drive
Cambridge, OH 43725
P 800.PICOMA1
F 740.439.4160

info@picoma.com
picoma.com

