

SpeedCouple Pre-installed Elbow Coupling



SpeedCouple is a pre-installed elbow coupling that is ideal for tight spaces. SpeedCouple is available on rigid steel elbows, standard elbows and special radius elbows in trade sizes 2-6.

Listing

SpeedCouple pre-installed elbow couplings are listed to UL-514B.

SpeedCouple rigid steel elbows are listed to UL-6 and are manufactured and UL® Listed to both U.S. and Canadian requirements.



Locations

SpeedCouple is not approved for wet locations. Picoma's standard conduit and standard couplings are approved for wet and hazardous locations, including direct burial.

SpeedCouple is not approved for hazardous locations.

SpeedCouple rigid steel elbows are permitted in installations and locations covered by National Electrical Code® Article 344—Rigid Metal Conduit. Reference Article 344.42 for threadless couplings and connectors.

Coatings

SpeedCouple is zinc-electroplated.

Miscellaneous

The conduit must be wrench tightened.

SPEEDCOUPLE 90° ELBOWS WEIGHTS, DIMENSIONS AND PACKAGING

TRADE SIZE	MIN. RADIUS	OFFSET	STRAIGHT	WEIGHT PER ELBOW	WEIGHT PER ELBOW WITH COUPLING	STANDARD CARTON QTY.
	in.			Each	Each	
2	9.5	14.54	5.04	6.70	7.58	5
2½	10.5	17.00	6.50	12.00	13.76	Bulk
3	13	19.67	6.67	19.00	20.98	Bulk
3½	15	22.72	7.72	28.00	30.65	Bulk
4	16	23.94	7.94	31.00	34.09	Bulk
5	24	34.90	10.90	68.00	71.97	Bulk
6	30	45.50	15.50	114.00	119.25	Bulk

SUBMITTAL INFORMATION

PROJECT: _____ CONTRACTOR: _____ DATE: _____

ENGINEER: _____ SPECIFICATION REFERENCE: _____ SYSTEM TYPE: _____

LOCATIONS: _____ COMMENTS: _____

PIC-010424