# **Galvanized Steel Rigid Elbows**

Submittal Sheet



Picoma's galvanized steel rigid elbows are made in America to ensure the ultimate physical protection. Made from hot-dip galvanized steel rigid metal conduit, our rigid elbows are tough enough for use in outdoor applications, energy and manufacturing plants, and corrosive environments. Standard and special large-radius elbows are available to meet the needs of any project.

### Listing

Picoma's galvanized steel rigid elbows are UL® Listed to UL-6 and manufactured in accordance with ANSI® C80.1.



#### Locations

Picoma's galvanized steel rigid elbows meet the requirements of National Electrical Code<sup>®</sup> Article 344 for use in indoor and outdoor locations and in wet and dry locations, including Class 1 Division 1 hazardous locations. They may be used for both exposed and concealed installations.

#### Coatings

Picoma's galvanized steel rigid elbows are hot-dip galvanized on both the interior and exterior to defend against corrosion. They then receive a passivation coating for extra protection.

### SUBMITTAL INFORMATION

PROJECT:			CONTRACTOR:	DATE:			
ENGINEER:			SPECIFICATION REFERENCE: SYSTEM TYPE:				
LOCATIONS:							
Ē	9208 Jeffrey Drive Cambridge, OH 43725 P 800.PICOMA1 F 740.439.4160	info@picoma.com picoma.com		<b>picoma</b> ® A ZEKELMAN COMPANY			


# **Galvanized Steel Rigid Elbows**


# Submittal Sheet



### 90° ELBOWS

TRADE SIZE	UL MIN. RADIUS**	OFFSET (FIG. 1)	UL MIN. STRAIGHT (FIG. 2)**	WEIGHT PER 100	STANDARD CARTON QTY.	
	in.	in.	in.	lbs.		
1⁄2	4	5 1/8	11⁄2	70	50	
3/4	4 1/2	7	11⁄2	112	50	
1	5 3⁄4	8 3⁄4	1 7⁄8	192	25	
1¼	7 1⁄4	10 3⁄4	2	320	20	
1½	81⁄4	12 1⁄4	2	413	15	
2	9 1⁄2	14 ½	2	670	10	
21⁄2*	10 1⁄2	17	3	1200	Bulk	
3*	13	19 5⁄8	3 1/8	1900	Bulk	
<b>3</b> ½*	15	22 3⁄4	3 1⁄4	2800	Bulk	
4*	16 23 7/8		3 3/8	3100	Bulk	
5*	24	34 1/8	3 5/8	6800	Bulk	
6*	30	45½	3 3⁄4	11400	Bulk	





 Trade sizes 2½ and larger shipped in palletized cartons or bulk. Palletized and bulk elbows supplied with a thread protector on each end and UL label affixed.
\*\* Minimum dimension per UL-6.


### **SPECIAL LARGE-RADIUS 90° ELBOWS**

TRADE SIZE	12" RADIUS	15" RADIUS	18" RADIUS	24" RADIUS	<b>30</b> " RADIUS	<b>36</b> " RADIUS	42" RADIUS	<b>48</b> " RADIUS	60" RADIUS
1	4	6	5	6	9	9	12	13	_
1¼	6	7	7	9	12	13	16	18	-
1½	8	9	10	11	15	16	19	21	-
2	10	10	11	14	20	22	24	26	-
21/2	-	19	18	23	27	32	39	44	_
3	-	25	28	32	37	45	52	57	-
3 1/2	_	Standard Radius	31	35	42	54	62	69	_
4	-	-	38	45	54	64	73	81	90
5	_	_	_	Standard Radius	85	94	100	120	136
6	-	-	_	-	Standard Radius	131	140	160	182

Numbers in table above represent weight in pounds of special-radius elbows we offer.

## DIMENSIONS OF SPECIAL LARGE-RADIUS 90° ELBOWS

TRADE SIZE	1-2 ½	1-3	1-4	1-4	1-5	1-6	1-6	1-6
When Radius "A" Is	12 "	15"	18 "	24"	30"	36"	42"	48"
Offset "C" Is	1'9"	2'0"	2'4"	2'11"	3'5"	3'11"	4'6"	5'0"
Straight End "D" Is	9"	9"	10 "	11 "	11 "	11 "	12 "	12 "
Length Unbent Is	3'0"	3'6"	4'0"	4'11"	5'9"	6'6"	7'6"	8'4"



PIC-010424



9208 Jeffrey Drive Cambridge, OH 43725 P 800.PICOMA1 F 740.439.4160

info@picoma.com picoma.com

